



Parafuso “U”

Tornillo “U”

“U” Bolt



Referência	Ruptura	Dimensões I Dimensiones I Dimensions						Peso
Nº Catalogo	Rotura	(mm)						Peso Neto
Cat. Number	Ultimate Strength							Net Weight
	(kN)	A	B	Ci	Cr	Porcas Tuercas Nut	Arruelas Arandelas Washer	(kg)
F3016-09	80	60	5/8"	250	100	4	2	1,022
F3016-10	80	60	5/8"	300	100	4	2	1,157
F3016-06	80	70	3/4"	180	110	4	4	1,182
F3016-02	80	80	3/4"	150	80	6	0	1,049
F3016-03	80	80	3/4"	180	80	6	0	1,182
F3016-07	100	50	5/8"	125	65	6	4	0,671
F3016-04	100	66	5/8"	100	65	6	0	0,559
F3016-08	100	70	5/8"	110	70	6	0	0,588
F3016-13	100	70	5/8"	130	70	6	0	0,654
F3016-28	120	70	5/8"	110	70	6	4	0,638
F3016-01	120	70	3/4"	130	85	6	4	1,066
F3016	120	80	3/4"	120	80	6	0	0,955
F3016-12	120	100	3/4"	220	100	4	4	1,403
F3016-29	120	120	3/4"	180	80	6	4	1,355

MATERIAL: Aço forjado galvanizado a quente
 Acero forjado galvanizado en caliente
 Forged steel, hot dip galvanized